

BTV SELF-REGULATING HEATING CABLE



nVent RAYCHEM BTV self-regulating trace heating cables provide freeze protection and process temperature maintenance, up to 150 °F/65 °C, of pipes/vessels without steam cleaning requirements. They withstand intermittent exposure to 185 °F/85 °C and are hazardous area approved. The polyolefin outer jacket (-CR) is suitable for mild inorganic solutions. The fluoropolymer outer jacket (-CT) provides high chemical resistance against aggressive organics and corrosives.

FEATURES

Simplified design in hazardous area: unconditional T6 class

Fast installation: cut-to-length, multiple overlaps allowed, meter markings, user-friendly connections kits

Safe and efficient in operation: no overheating, uniform pipe temperatures, energy saving technology

Reliable during long life: 10 year product warranty available, maintenance free

SPECIFICATIONS

Max Maintain or Continuous Exposure Temperature, Power On/Off	150 °F
Max Intermittent Exposure Temperature, Power On/Off	185 °F
Ground Path Type	Braid
Area Classification	Non-Hazardous; Hazardous

Catalog Number	Item Name	Supply Voltage	Outer Jacket Material	Nominal Power Output @ 50°F, 120V	Nominal Power Output @ 50°F, 240V
013331-000	3BTV1-CR	100 – 130 V	Modified Polyolefin	3 W/ft	W/ft
208489-000	5BTV1-CR	100 – 130 V	Modified Polyolefin	5 W/ft	W/ft
313747-000	5BTV1-CT	100 – 130 V	Fluoropolymer	5 W/ft	W/ft
414809-000	5BTV2-CR	200 – 277 V	Modified Polyolefin	W/ft	5 W/ft
469145-000	3BTV2-CT	200 – 277 V	Fluoropolymer	W/ft	3 W/ft
487509-000	5BTV2-CT	200 – 277 V	Fluoropolymer	W/ft	5 W/ft
893301-000	3BTV1-CT	100 – 130 V	Fluoropolymer	3 W/ft	W/ft
914279-000	3BTV2-CR	200 – 277 V	Modified Polyolefin	W/ft	3 W/ft
002349-000	10BTV1-CR	100 – 130 V	Modified Polyolefin	10 W/ft	W/ft
008633-000	8BTV2-CT	200 – 277 V	Fluoropolymer	W/ft	8 W/ft

Catalog Number	Item Name	Supply Voltage	Outer Jacket Material	Nominal Power Output @ 50°F, 120V	Nominal Power Output @ 50°F, 240V
413851-000	8BTV1-CR	100 – 130 V	Modified Polyolefin	8 W/ft	W/ft
479821-000	8BTV2-CR	200 – 277 V	Modified Polyolefin	W/ft	8 W/ft
481491-000	8BTV1-CT	100 – 130 V	Fluoropolymer	8 W/ft	W/ft
516277-000	10BTV1-CT	100 – 130 V	Fluoropolymer	10 W/ft	W/ft
567513-000	10BTV2-CT	200 – 277 V	Fluoropolymer	W/ft	10 W/ft
677245-000	10BTV2-CR	200 – 277 V	Modified Polyolefin	W/ft	10 W/ft

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258
 Fax +1.800.527.5703
thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511
 Fax +32.16.213.604
thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688
 Fax +86.21.5426.3167
cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800
 Fax +1.713.868.2333
thermal.info@nvent.com



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.