

# QTVR SELF-REGULATING HEATING CABLE



nVent RAYCHEM QTVR self-regulating trace heating cables are suitable for freeze protection of large pipes/vessels with high heat loss, and for process temperature maintenance applications without steam-cleaning requirements, up to 225 °F/110 °C. The fluoropolymer outer jacket (-CT) provides high chemical resistance against aggressive organics and corrosives.

## FEATURES

Simplified design for hazardous areas: unconditional T4 class

Fast installation: cut-to-length, multiple overlaps allowed, meter markings, user-friendly connections kits

Safe and efficient in operation: no overheating, uniform pipe temperatures, energy saving technology

Reliable during long life: 10 year product warranty available, maintenance free

## SPECIFICATIONS

<b>Max Maintain or Continuous Exposure Temperature, Power On/Off</b>	225 °F
<b>Max Intermittent Exposure Temperature, Power On/Off</b>	225 °F
<b>Ground Path Type</b>	Braid
<b>Outer Jacket Material</b>	Fluoropolymer
<b>Area Classification</b>	Non-Hazardous; Hazardous

Catalog Number	Item Name	Supply Voltage	Nominal Power Output @ 50°F, 120V	Nominal Power Output @ 50°F, 240V
040615-000	15QTVR2-CT	200 – 277 V	W/ft	16 W/ft
148345-000	15QTVR1-CT	100 – 130 V	16 W/ft	W/ft
259951-000	10QTVR1-CT	100 – 130 V	12 W/ft	W/ft
391991-000	10QTVR2-CT	200 – 277 V	W/ft	12 W/ft
498703-000	20QTVR1-CT	100 – 130 V	20 W/ft	W/ft
988967-000	20QTVR2-CT	200 – 277 V	W/ft	20 W/ft

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials.

Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America**

Tel +1.800.545.6258  
Fax +1.800.527.5703  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

**Europe, Middle East, Africa**

Tel +32.16.213.511  
Fax +32.16.213.604  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

**Asia Pacific**

Tel +86.21.2412.1688  
Fax +86.21.5426.3167  
[cn.thermal.info@nvent.com](mailto:cn.thermal.info@nvent.com)

**Latin America**

Tel +1.713.868.4800  
Fax +1.713.868.2333  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**