

SINGLE-ENTRY POWER CONNECTION WITH JUNCTION BOX

nVent RAYCHEM JBS-100 is a junction box used to connect power to one nVent RAYCHEM BTV, QTVR, XTV, KTV or VPL industrial parallel heating cable. Offered in three versions, customized for local installation practices, each are also available with a power indicator. JBS-100-E, JBS-100-L-E; JBS-100-EP, JBS-100-L-EP; JBS-100-A, JBS-100-L-A.

FEATURES

Simple and fast to install, spacious boxes with front access, captive lid screws and robust spring type terminals for secure fixing

Part of a modular component system, providing maximum flexibility

One range for all nVent RAYCHEM industrial parallel heating cables

Simplified design in hazardous area, integral part of system approval

Cold-applied: core sealing boot with non-curing sealant; no heat gun, no hot work permit needed

Reliable during long life: 10 year extended product warranty available, maintenance free

SPECIFICATIONS

| | |
|------------------------------------|--------------------------------|
| Max Conductor Cross Section | 0.0155 in ² |
| For Ex-Zone Gas | 1, 2 |
| Inlet Quantity | 2 |
| Connection Clamp Quantity | 3 |
| Cable Entry | 3/4" |
| Depth | 3.54 in |
| Width | 4.72 in |
| Height | 9.5 in |
| For Ex-Zone Dust | 21, 22 |
| Connection Type | Cold Applied |
| Material | Glass Fiber Reinforced Polymer |
| Area Classification | Non-Hazardous; Hazardous |
| IP Rating | IP66 |
| Knockouts Included | No |
| Mounting | On Pipe |

Cover Attachment Screwed
Halogen Free Yes

| Catalog Number | Item Name | Ambient Temperature | Light Indication Included | Earth Plate Included | Below Insulation |
|----------------|-------------|---------------------|---------------------------|----------------------|------------------|
| 085947-000 | JBS-100-A | -40 to 133 °F | No | No | No |
| 944699-000 | JBS-100-L-A | -40 to 104 °F | Yes | No | No |
| C26470-000 | JBS-100-A6 | -40 to 133 °F | No | No | No |

ADDITIONAL PRODUCT DETAILS

Localized versions may exist with limited approvals and different part numbers. Contact your local sales representative.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258
Fax +1.800.527.5703
thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511
Fax +32.16.213.604
thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688
Fax +86.21.5426.3167
cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800
Fax +1.713.868.2333
thermal.info@nvent.com



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.